कार्यालय, नगर पालिक निगम, कोरबा (छ.ग.)

मुरूय कार्यालय - साकेत भवन, जाई.टी.जाई. चौक, कोरबा (छ.म.)

सर्व<u>मंगला/</u>बांकीमोंगरा जोन

फा.क./783 से 786, 774, 775, 787, 780,788, 795, 690, 667, 697/निर्माण(सर्वमंगला/बांकीमोंगरा जोन)/2023/कोरबा, दिनांक 01.012024

निविदा आमंत्रण सूचना

नगर पालिक निगम कोरबा द्वारा लोक निर्माण विभाग से एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से निम्नलिखित कार्य हेतु प्रमुख अभियन्ता लोक निर्माण विभाग, रायपुर द्वारा प्रचलित PWD Building SOR 01.01.2015 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) कम अधिक या समान दरों पर तथा शेड्युल अनुसार आयटम दरों पर निम्नलिखित निर्माण कार्यों हेतु मैन्युअल निविदा वेबसाईट से डाउनलोड कर बंद–लिफाफा पद्धति के माध्यम से आमंत्रित की जाती है :–

निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने अंतिम तिथि
 निविदा खुलने की अंतिम तिथि

23.01.2024 सायंकाल 3:00 बजे तक
 23.01.2024 सायंकाल 4:30 बजे से

क्र.	कार्य का नाम	प्राक्कलन राशि में	धरोहर राशि रू में	निविदा प्रपत्र का मूल्य	निविदा प्रपत्र	कार्यावधि	ठेकेदार का वर्ग	निविदा खुलने की अंतिम तिथि
1	वार्ड क्र. 54 मॉ सर्वमंगला मंदिर के पास संचालित वृद्धा आश्रम मे अन्य सुविधाओं का विस्तार कार्य। (विधायक प्रभारी मंत्री मद)	2,00,000/-	2,000/-	750/-	Form-A	02 비명	स्तक्षम श्रेणी	23.01.2024
2	यार्ड क्र. 61 कुसमुण्डा सामुदायिक भवन निर्माण (विधायक प्रभारी मंत्री मद)	15,00,000/-	11,300/-	750/-	Form-A	04 माह	सक्षम श्रेणी	23.01.2024
3	वार्ड क्र. ६१ कुसमुण्डा शिव मदिर के पास सांस्कृतिक मंच निर्माण सह शौचालय निर्माण कार्य। (विधायक प्रभारी मंत्री मद)	5,00,000/-	5,000/-	750/-	Form-A	03 माह	सक्षम श्रेणी	23.01.2024
4	वार्ड क्र. 61 कुसमुण्डा कुसमुण्डा दाई मंदिर के पास पक्का छत निर्माण कार्य। (विधायक प्रमारी मंत्री मंद)	5,00,000/-	5,000/-	750/-	Form-A	03 माह	सक्षम श्रेणी	23.01.2024
5	वार्ड क्र. 61 अलर्गत गायत्री मंदिर घौक के समीप यात्री प्रतीक्षालय व दो स्थानों पर बोर उत्खनन का कार्य। (पार्षद मद 2023–24) <i>(द्वितीय निविदा)</i>	7,00,000/-	5,300/-	750/-	Form-A	02 माह	सक्षम श्रेणी	23.01.2024
6	वार्ड क्र. C2 में मायत्री गरिर घुनचुनी मोहल्ला एवं शत्रुधन घर से राधेश्याम घर तक सी सी रोड निर्माण कार्य। (पार्षद मद 2023–24) (द्वितीय निविदा)	7,00,000/-	5,300/-	750/-	Form-A	02 माह	सक्षम श्रेणी	23.01.2024
7	यार्ड क्र. 62 धरमपुर गेवरा बस्ती मंच निर्माण कार्य धरमपुर में। (विधायक मद कटघोरा 2023–24)	3,50,000/-	3,500/-	7 50 /-	Form-A	02 माह	संधाम श्रेणी	23.01.2024
э	वार्ड क्र. 64 अंतर्गत घुडदेवा में सामुदायिक भवन का संधारण एवं नयी सुविधाओं की व्ययस्था कार्य। (एल्डरमेन मद) (द्वितीय निविदा)	6,00,000/-	4,500/-	750/-	Form-A	02 माह	सक्षम श्रेणो	23.01.2024
9	वार्ड क ea एस एल.आर एम सेटर अंतर्गत 10 नग कम्पोस्ट पीट एवं शेख का निर्माण कार्य। (15वें वित्त आयोग ठोस अपशिष्ट प्रबंधन)	3,55,000/-	3,600/-	750/-	Form-A	02 माह	सक्षम श्रेणी	23.01.2024

2								
10	वार्ड क. 59 खम्हरिया अंतर्गत सार्वजनिक भवन का मरम्मत एवं नई सुविधाओं की व्ययस्था (एल्डरमेन निधि 2023–24)	6,00,000/-	4,500/-	750/-	Form-A	02 माह	सन्नम श्रेणी	23.01.2024
11	यार्ड क. 65 कुदरीपारा तालाब के पास नाली एवं सी.सी. सडक का निर्माण कार्य। (अघोसेरचना मद 2021–22) (द्वितीय निविदा)	8,00,000/-	6,000/-	750/-	Form-A	०३ माह	सक्षम श्रेणी	23.01.2024
12	वार्ड क. ६५ अंतर्गत पदमा मोहल्ला में नाली का मरम्मत कार्य। (मरम्मत संधारण मद) (द्वितीय निविदा)	3,99,000/-	4,000/-	750/-	Form-A	C2 माह	रादान श्रेणी	23.01.2024
13	वार्ड क. ६५ कुदरीपारा में नाली एवं कलवर्ट का मरम्मत कार्य। (मरम्मत संधारण मद) (द्रितीय निविदा)	3,91,300/-	4,000/-	750/-	Form-A	02 माह	संदाम श्रेणी	23.01.2024
	11	10 मवन का मरम्मत एवं नई सुविधाओं की य्यवस्था (एल्डरमेन निधि 2023-24) वार्ड क. 65 कुदरीपारा तालाब के पास नाली एवं सी.सी. सडक का निर्माण कार्य। (अघोसंरचना मद 2021-22) (द्वितीय निविदा) वार्ड क. 65 अतर्गत पदमा मोहल्ला मे नाली का मरम्मत कार्य। (मरम्मत संघारण मद) (द्वितीय निविदा) वार्ड क. 65 कुदरीपारा मे नाली एवं कलवर्ट का मरम्मत कार्य। (मरम्मत संघारण मद) वार्ड क. 65 कुदरीपारा मे नाली एवं कलवर्ट का मरम्मत कार्य। (मरम्मत संघारण मद)	10 मवन का मरम्मत एवं नई सुविदाओं की रेयवस्था (एल्डरमेन निधि 2023-24) 6,00,000/- यार्ड क. 65 कुदरीपारा तालाब के पास नाली एवं सी.सी. सडक का निर्माण कार्य। (अघोसरचना मद 2021-22) (दितीय निविदा) 8,00,000/- 11 एवं सी.सी. सडक का निर्माण कार्य। (अघोसरचना मद 2021-22) (दितीय निविदा) 8,00,000/- 12 वार्ड क. 65 अवर्गत पदमा मोहत्ला मे नाली का मरम्मत कार्य। (मरम्मत संघारण मद) (दितीय निविदा) 3,99,000/- 12 वार्ड क. 65 अवर्गत पदमा ने नाली एवं कलवर्ट 3,91,300/- 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/-	10 मवन का मरम्मत एवं नई सुविदाओं की रु.00,000/- 4,500/- यार्ड क. 65 कुदरीपारा तालाब के पास नाली यार्ड क. 65 कुदरीपारा तालाब के पास नाली 6,00,000/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 12 वार्ड क. 65 अतर्गत पदमा मोहत्त्सा मे नाली 3,99,000/- 4,000/- 12 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,99,000/- 4,000/- 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/-	10 मवन का सरम्मत एवं नई सुविदाओं की 6,00,000/- 4,500/- 750/- य्यवस्था (एल्डरमेन निधि 2023-24) वार्ड क. 65 कुदरीपारा तालाब के पास नाली 8,00,000/- 6,000/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- 12 वार्ड क. ६५ अवर्गत पदमा मोहत्ला मे नाली 3,99,000/- 4,000/- 750/- 12 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/- 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/-	10 मवन का मरम्मत एवं नई सुवियाओं की रु.00,000/- 4,500/- 750/- Form-A यार्ड क. 65 कुदरीपारा तालाब के पास नाली एवं सी.सी. सडक का निर्माण कार्य। (अघोसरचना मद 2021-22) (दितीय निविदा) 8,00,000/- 6,000/- 750/- Form-A 11 एवं सी.सी. सडक का निर्माण कार्य। (अघोसरचना मद 2021-22) (दितीय निविदा) 8,00,000/- 6,000/- 750/- Form-A 12 वार्ड क. 65 अंतर्गत पदमा मोहत्ला मे नाली का मरम्मत कार्य। (मरम्मत संघारण मद) (दितीय निविदा) 3,99,000/- 4,000/- 750/- Form-A 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/- Form-A	10 मवन का मरम्मत एवं नई सुविधाओं की 6,00,000/- 4,500/- 750/- Form-A 02 माह यवस्था (एल्डरमेन निधि 2023–24) 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- Form-A 02 माह 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- Form-A 03 माह 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- Form-A 03 माह 11 एवं सी.सी. सडक का निर्माण कार्य। 8,00,000/- 6,000/- 750/- Form-A 03 माह 11 एवं क. ६५ अवर्गत पदमा मोहल्ला मे नाली 3,99,000/- 4,000/- 750/- Form-A 02 माह 12 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/- Form-A 02 माह 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/- Form-A 02 माह	10 मवन का मरम्मत एवं नई सुवियाओं की 6,00,000/- 4,500/- 750/- Form-A 02 माष्ठ संक्षम श्रेणी 11 एवं सी.सी. सडक का निर्माण कार्य। (एल्डरमेन निधि 2023-24) 8,00,000/- 6,000/- 750/- Form-A 02 माष्ठ संक्षम श्रेणी 11 एवं सी.सी. सडक का निर्माण कार्य। (अग्रोसरचना मद 2021-22) (द्वितीय निविदा) 8,00,000/- 6,000/- 750/- Form-A 03 माह संक्षम श्रेणी 11 एवं सी.सी. सडक का निर्माण कार्य। (अग्रोसरचना मद 2021-22) (द्वितीय निविदा) 8,00,000/- 6,000/- 750/- Form-A 03 माह संक्षम श्रेणी 12 वार्ड क £5 अंतर्गत पदमा मोहत्सा मे नाली 3,99,000/- 4,000/- 750/- Form-A 02 माह संक्षम श्रेणी 12 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,99,000/- 4,000/- 750/- Form-A 02 माह संक्षम 13 का मरम्मत कार्य। (मरम्मत संघारण मद) 3,91,300/- 4,000/- 750/- Form-A 02 माह संक्षाम

निविदा की शर्तः-

- 1. निविदा दरें प्रचलित सी.एस.आर.से कम या अधिक प्रतिशत् दूरों पर दिया जावे सी.एस.आर.के अंतर्गत के आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त मानी जावेगी।
- निविदा के दस्तावेज हाथो-हाथ न लिया जाकर रजिस्टर्ड पोस्ट अथवा स्पीड पोस्ट से प्राप्त किया जावेगा। अन्य माध्यमों यथा कोरियर सर्विस, 2 साधारण डाक इत्यादि से प्राप्त अथवा समयावधि के पश्चात् प्राप्त निविदाओं पर विचार नहीं किया जावेगा। निविदा आयुक्त, नगर-मालिक निगम, कोरबा आई.टी.आई. कॉलोनी रामपुर, कोसाबाड़ी जिला-कोरबा (छ.ग.) पिन नं.-495677 के पते पर मेजना होगा। निर्धारित तिथि को सायं 3:00 के पश्चात प्राप्त निविदाएँ स्वीकार नहीं किए जावेंगे।
- निविदा प्रपन्न नगर पालिक निगम, कोरबा के वेबसाईट www.korbamunicipal.in/uad.cg.gov.in डाउनलोड किया जाकर नवीन निविदा प्रपन्न 3 Form - A/B/ABC (जारी दिनॉक तक समस्त संशोधनों के साथ) निर्धारित शुल्क की डीडी के साथ संबंधित कार्य का नाम पूर्ण विवरण सहित भरकर भेजना होगा।
- निविदा प्रपत्र बंद-लिफाफा पद्धति से मान्य किया जावेगा जो निम्नानुसार होगाः-4
 - प्रथम लिफाफा में ठेकेदार का जीवित पंजीयन प्रमाण पत्र, आयकर चुकता प्रमाण पत्र, निविदा सूचना आमंत्रण में उल्लेखित अन्य (अ) दस्तावेज के साथ निविदा सूचना जारी होने के पश्चात् दिनॉक का निर्धारित निविदा प्रपत्र शुल्क का डीडी, शफ्य पत्र राशि रू 100/- के नान ज्यूडिशियल स्टाम्प पेपर पर जिसमें संबंधित कार्य का नाम एवं कार्य की निविदा क अंकित हो निविदाओं में निविदाकार को फिजिकल दरतावेज के साथ प्रेषित करना अनिवार्य होगा एवं अमानत राशि का टी.डी.आर. / एफ.डी.आर. नगद निमम कोष में जमा कर जो कि आयुक्त, नगर पालिक निगम कोरबा के नाम पर देय होगा प्रस्तुत करना होगा।
 - द्वितीय लिफाफा में ठेकेदार द्वारा भरा हुआ निविदा प्रपन्न होगा। (ब)
 - (स) तृतीय लिफाफा में उपरोक्त दोनो लिफाफाएँ होगी तथा आवश्यकता पड़ने पर मूल अभिलेख प्रस्तुत करना होगा।
- जिन ठेकेदारों द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा नगर 5 पालिक निगम (साडा) के हित के विरूद्ध कार्य किया गया हो उन्हें निविदा भरने की पात्रता नहीं होगी।
- निविदा प्रपत्र प्राप्त करने हेतु इच्छुक ठेकेदारों को आवेदन पत्र के साथ उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनरशीप डीड) की सत्य प्रतिलिपि, पूर्व में इस प्रकार की किए गए कार्यों की प्रमाणित सूची, उपलब्ध तकनीकी अमले की जानकरी पिछले वित्तीय वर्ष का आय चुकता प्रमाण पत्र, पेन नम्बर, जीएस.टी. पंजीयन, शपथ पत्र (मूल प्रति) एवं प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण मन्न, कर्मचारी मविष्य निधि संगठन, कर्मचारी, राज्य बीमा निगम रायपुर, रो पंजीयन, एवं विस्तृत निविदा आमत्रण सुवना (एनआईटी) हरताक्षरयुवत एवं निर्धारित प्रारूप में निविदा आमंत्रण सूचना के कंडिका क. 04 के लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।
- कार्य हेतु लिफाफे पर कार्य का नाम निविदा आमंत्रण सूचना कमॉक, निविदा खुलने की तिथि स्पष्ट रूप से लिखकर भेजना होगा। 7
- निविदाकार का यह दायित्व है कि वे निविदा मरने के पूर्व स्थल का स्वयं निरीक्षण कर लेवें ताकि प्रारंभ करने में किसी प्रकार की कठिनाई न हो। 8
- निधारित निविदा प्रपत्र में उल्लेखित कडिकाएँ स्वमेव लागू मानी जावेगी एवं निविदा आमंत्रण सूचना निविदा का ही भाग माना जावेगा। 9
- निर्धारित प्रारूप में निविदा प्रपन्न, निविदा प्रपन्न शुल्क, अमानत राशि, निविदा आमंत्रण सूचना पत्र में उल्लेखित दस्तावेज सही पाए जाने पर ही निविदा दर संबंधी लिफाफा खोला जावेगा अन्यथा निविदा निरस्त कर दी जावेगी।
- 11. ठेकेदार को अपनी दरें शब्दों एवं अंकों में लिखना अनिवार्य होगा।
- 12. शासन के विभिन्न विभागों जैसे खजिन विभाग, श्रम विभाग, समाज कल्याण विभाग इत्यादि विभागों द्वारा समय-समय पर जारी निर्देशो/आदेशो के पालन की समस्त जिम्मेदारी संबंधित ठेकेदार की होगी।
- 13. ठेकेदार यदि कार्य को अपूर्ण स्थिति में छोड़ता है, तो निविदा प्रपन्न में उल्लेख अनुसार इस संबंध में प्रावधान के अंतर्गत कार्यवाही की जावेगी।
- 14. कार्य प्रारंग नहीं करने अथवा अपूर्ण स्थिति में छोड़ने पर निगम द्वारा ठेकेदार के विरुद्ध तत् समय में एम.आई.सी. द्वारा स्वीकृत प्रस्ताव के अधीन कार्यवाही की जावेगी जिसकी संपूर्ण जवाबदारी ठेकेदार की होगी।
- 15. सफल निविदा दाता से अनुबंध के समय अतिरिक्त परफार्मेंस राशि जमा कराई जावेगी जबकि निविदा की दरों में काफी कमी हो जैसे निविदादाता को निविदा दर एवं अनुमानित लागत से 10 प्रतिशत से अधिक निविदा दर होने पर सफल निविदादाता को निविदा दर एवं अनुमानित लागत के 90 प्रतिशत अंतर की राशि के समतुल्य परफार्मेंस गारंटी के रूप में राष्ट्रीयकृत बैंक का एफ डी.आर. /टी.डी.आर. ऑफिस टाईम डिपॉजिट अथवा एन.एस.सी.जो कि आयुक्त नगर पालिक निगम कोरबा के नाम से देय होगा, जौ गांग तिथि से 15 दिवस के मीतर जमा करना अनिवार्य होगा। उपरोक्त राशि को जमा न करने की दशा में निविदा निरस्त कर दी

- 10. सम्पूर्ण किये गये कार्यों के लिये 5 प्रतिशत सुख्या राशि रनिंग देयकों के साथ 01 वर्ष हेतु साथ ही मरम्मत एवं संघारण प्रवृत्ति के कार्यों को छोड़कर 5 प्रतिशत पृथक से 03 वर्ष की गारंटी के लिये परफामेंस सिवयूरिटी के रूप में सेकी जावेगी। (मरम्मत संघारण मद के कार्यों को छोड़कर)
- 17. निविदा में भाग लेने वाले ठेकेदारों को छ.ग. भवन और अन्य सन्निर्माण कर्मकार (नियोजन एवं सेवा शर्तों का विनियमन) अधिनियम 1996 एवं तद्ध्रंतर्गत निर्धारित नियमों के तहत् पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का 1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।
- 18. निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नगर निगम या अन्य विमामों में किये जा रहे कार्यों का विवरण संशि सहित मुल प्रति में वैध शपथपत्र कंडिका क. 04 के प्रथम लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।
- 19. ईट से संबंधित निर्माण कार्यों में पलाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।
- 20. निविदा प्रपत्र अहत्त्तांतरणीय होया एवं सरातं निविदाओं पर विवार नहीं किया जावेगा।
- 21. निविदा के संकंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त के द्वारा अधीनस्थ अधिकारियों का निर्णय अंतिम एवं सर्वमान्य होगा।
- 22. निविदा प्रपन्न ध्वतल-। के क्लॉज नम्बर 11 अनुसार एस्केलेशन देय नहीं होगा।
- 23. निविदा स्वीकृत करने अथवा अर्स्वीकृत करने का अधिकार आयुक्त, नगर पालिक निगम के पास सुरक्षित रहेगा।
- 24. निविदा खुलने की तिथि में अवकाश होने पर आगामी तिथि (कार्य दिवस) को निविदा संबंधी कार्यवाही मानी जावेगी।

नोट:-

- अमानत राशि के रूप में एफ.डी.आर. /टी.डी.आर. अथवा नगद जमा रसीद पृथक से लिफाफे में स्वीकार किए जावेंगे आयुक्त, नगर पालिक निगम, कोरदा के नाम पर देय हो।
- उपरोक्त तिथियों में किसी भी तिथि को शासकीय/स्थानीय अवकाश होने की स्थिति में अगले कार्य दिवस को निर्धारित तिथि समय एवं स्थान माना जावे।
- प्रतिलिपि :-- प्रोग्रामर संचालनालय, नगरीय प्रशासन एवं विकास विमाग, नवा रायपुर छ.ग. को www. uad.cg.gov.in में अपलोड किये जाने हेतु प्रेषित।

नगर पालिक /निगम

गर पालिक गनगन कोरबा (छ.ग.)

(ठेकेदार के हस्ताक्षर)

नाम पूर्ण पता

6

मोबाईल नं.--

//03//

C FFICE OF THE NAGAR PALIK NIGAM, KORBA (C.G.) DETAILED ESTIMATE

Name Of Work :-वार्ड क. 64 अंतर्गत घुडदेवा में सामुदायिक भवन का संघारण एवं नयी सुविधाओं की व्यवस्था। (एल्डरमेन मद)

As Per SOR : - SCHEDULE OF RATES PUBLIC WORKS DEPARTMENT [PWD BUILDING - 01.01.2015]

S.N.	REF	ITEM DESCRIPTION	N	L	B	H/D	0.001		13 4 100 42	
1		Dismantling lime/ cement plaster				1 1/0	QTY	UNIT	RATE	AMOUNT
		or skirting at any height raking out								
		joints and cleaning the surface for					1			
		plaster including disposal of								
		rubbish within 50								
		metres lead.								
		Shed	1	6.00	5.00		30.00			
			2	6.00	3.20	1	38.40			
			2	5.00	3.20		32.00			
		2	1	6.40	3.60		23.04			
			1	6.40	0.60		3.84			
			2	5.40	3.60		38.88			
			2	-	0.40		5.12			
			2	5.40	0.40	1	4.32			
			2		0.40		4.80			
			2	5.00	0.40		4.00			
		Commu. Hall	1	6.00	12.00		72.00			
			2	6.00	3.20		38.40			
			2	12.00	3.20		76.80			
			2	6.40	3.80		48.64			
			2	12.40	3.80		94.24			
			-4	3.00	3.20		38.40			
			4		3.40		46.24			1
			4	3.40	3.40		46.24			
			4		3.40		40.80			
			4	2.40	3.40		32.64			
			2	6.40	0.40		5.12			
			2		0.40		9.92			
			2	6.00	0.40		4.80			
			2	12.00	0.40		9.60			
						Total	748.24			
		Deduction (-)								
		C.E	2	4.00	2.40		19.20			
		W	12	1.50	1.50		27.00			
		D	6	1.00	2.10		12.60			
		C.E.	2	5.00	2.40		24.00			
		D	4	0.80	2.10		6.72			
						Total	89.52			
						Total	658.72	sqm	11.00	7245.92

Dail.	N annon		-	Market School a	Vicial Statements	Contraction of the local division of the		220703 cmm v1		
15	18/1	Dismantling steel work in built-up	_				And the set of the set of the set			
	and the second	section in angles, channels, flats								
		t section and T-section including								
		all gusset plates, bolts, nuts,								
		cutting rivets,								
		welding etc., including								
		dismembering and stacking within								
		50 metres lead								
Annual		so metres lead	Including in	AND DESCRIPTION OF	Marine Colonard	ANTIGATION CONTRACTOR	structure print program	SCHEDRED HERE	THE DOWN PERSON PERSON AND	and the second se
			LITER DOTTING	bedweetspecture.	STOCK ST. ST. ST. ST.	Repairing the second	500.00	kß	1,00	600.00
3	10'43	Demolishing cement concrete								
		including disposal of material								
		within 50								
		metre lead.								
	43.2	1:3:6 or richer mix		and a state of the	And a second sec	Contraction of the local division of the loc		Fight Manager		
			interpretation in the	5.00	6.00	0.00	2.40	Cardineers Starts	Support to the Construction of the State	ter planter years by a return
	Sector Descriptions with the		annan i	12.00	6.00	0.00	per and stilling there are not been all	and the second	production design in which	
	-	And the second	senses free	sceneror and a second second	Scand Spectromences of	STREET, STREET	6.76	ONE CONTRACTOR	1.00.00000445294030-00299	
			torenistini 12	3.00	3.00	0,00	0.72	and an and a second second	Tributuation estations	The party of the second s
			2	2.40	3.00	0,08	1,15	stricture are	NO INVESTIGATION OF THE OWNER OF T	
			mananame	description of the local division of the	- Entertaine Grandward and and	Total	10.03	Cum	549,00	5507,57
4	11.41	Providing and fixing chicken mesh								
		weighting not less than 250 gms/								
		sqm as per IS : specification in the								
		required width with 40mm long								
		steel								
		nails on vertical and horizontal								
		surface near R.C.C. and brick walls								
		junctions including scaffolding and								
		all lead and lifts etc. complete								
		hofene whet and miss etc. complete								
(before plastering upto 10mts in								
		height.	-			- No. Annual Concernment of		Contraction of Contraction of	Contraction of the second second	
-					-		329.36	sqm	86.00	28324.96
5	11.1	Providing and making 6mm thick						and the second s	No. Control of the local sector	THE REPORT OF THE REPORT OF THE REPORT OF
		cement plaster of mix:								
	1.2	In Cement mortar 1:4 (1 cement : 4				Sector States	148.91	Sqm	87.00	12955.17
		fine sand)							07100	14/0011/
6	11.2	Providing and making 12mm thick						-	NAMES OF TAXABLE PARTY.	and the second se
		cement plaster of mix								
	2.3	In Cement Mortar 1:5 (1 cement : 5						-		
		fine sand)								
				F 00	0.00				Restance of the second	
			2	5.00	3.20		32.00		One of the other o	
			1	6.00	3.20		19.20			
			1	6.00	0.80		4.80		Construction Construction Construction Construction Construction Construction Construction Construction Constru	
			2	5.00	0.40		4.00			
			2	6.00	0.40		4.80			
			2	6.00	3.20		38.40			
			2	12.00	3.20		The second s			
_					and the owner whether the second in the		76.80			
-		````	4	3.00	3.20		38.40			
			2	3.00	3.00		18.00			
			2	3.00	3.00		18.00			
 			2	6.40	0.40		5.12			
┣_			2	12.40	0.40		9.92			
-						Total	COLUMN & DAVIS OF THE OWNER OWNER OF THE OWNER OWN			
						rotat	269.44			
		Deduction-		1.00						
		Deduction-	1	4.00	2.40		9.60			
		Deduction-	1 6 3	1.50	2.40 1.50 2.10		9.60 13.50			

In Case or any uscre

			1	5.00	2.10		10.50			
10		X.	2	0.80	2.10		3.36			
	- (·					Total	43.26			
			-			Total	226.18	sqm	96.50	21826.37
7	113	Providing and making 15mm thick	-							
<i>'</i>	11.5	cement plaster on the rough side								
		of single or half brick wall of mix:								
		of single of null brief wan er an								10
-	3.3	In Cement Mortar 1:5 (1 cement : 5					283.63	Sqm	113.00	32050.19
	5.5	fine sand)								
8	916	Providing and fixing M.S. frames of								
Ĭ	2.10	doors, windows, ventilators and								
		cupboards joints mitred and				1				
		welded with 15x3 mm lugs 10cm								
		long embedded in cement								
		concrete blocks 15x10x10cm of								
		grade M-10 or with wooden plugs								
		and screws or with								
	16.2	Angle-iron frames								
	10.2						100.00	kg	73.50	7350.00
9	913	Providing and fixing steel door/					,			
,	2.10	window with M.S. sheet 1mm								
		thick, frame of angle iron, diagonal								
		braces of angle/ flat iron of								
		suitable size, 3.00 mm								
		M.S. gusset plates at junctions and								
		corners, all necessary fittings								
		complete including applying a								
		priming coat of red oxide zinc								
		chromate								
-							300.00	kg	75.00	22500.00
10	4.13	Grading roof for water proofing								
		treatment with:								
	13.1	Cement concrete 1:2:4 (1 cement :								
		2 coarse sand : 4 graded stone								
		aggregate 20 mm nominal size)								
-			1		12.00	0.03				
			1		3.00	0.03				
			2		3.40	0.03				
			1	5.00	6.00	Total		cum	3817.00	15046.61
						Total	5.74	cum	5017.00	13040.01
11	7.5	Brick work with modular fly-ash								
		lime bricks (FaLG Bricks)								
		confirming to IS:12894-2002 of class designation 4.0 in foundation								
		and plinth in:		ļ						
	5.3	Cement Mortar 1:5 (1 cement : 5		1						
		coarse sand)		F 00	1.20	0.40	4.80			+
			2							
-			2							+
-			<u> </u>	5.00	0.60				2250.00	26120.00
			L	l		Total	7.80	cum	3350.00	26130.00

1 a company	ß										
	12	57	Providing stainless steel railing/ grill made of S.S. flats, hollow S.S. pipe or square/ rectangular sections of approved design fixing in stair case, balcony or other places with metal fasteners and stainless steel bolts etc complete								-
		57.2	SS Grade 304								
								40.00	kg	525.00	21000.00
	13	3.1	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.								
		1.5	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).								
				1	10.00	2.00	0.10 Total	2.00		4073.00	8146.00
	14	3.2	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.				Total	2.00	Cum	4073.00	0140.00
		2.1	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).								
			Col	1	6.00	12.00		5.76			
				1 2	3.00 2.40	3.00 3.00		0.72			
				2	6.00	5.00	0.08	1.15			
					0.00	5.00	Total	10.03	Cum	4163.00	41763.22
	15	3.12	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete:					10.00	Cam	1103.00	+1/03.22
		12.1	Thermo-Mechanically treated bars FE 415					300.96	Kg	54.50	16402.32
	16	3.14	Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer.					25.00	Kg	43.50	1087.50



18 12.13 Providing and laying vitrified floor tiles with double charge/multi charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement mixed with matching pigment etc., complete. Image: Conforming to IS : 15622 of approved size, make, colour, shade		42									
Shutter consisting of frame made out of MS. tubes of 19 gauge thickness and size of 19 mm for top & bottom rails. MS. frame shall have a coat of steel primers of approved make and manufacture Image: Construct of Steel primers of approved make and manufacture 1522 Both side Pre-laminated panel PVC do shutter Image: Construct of Steel primers of approved make and manufacture Image: Construct of Steel primers of approved make and manufacture 18 12.13 Providing and laying vitrified floor tiles with double charge/ multi charge printing with water absorption less than 0.5% and conforming to 15: 15622 of approved make in all colours and shades and size mentioned below (+/ - 10mm), laid on 20mm thick cement mortar 1.4 (1 cement + 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Construct of Steel approved size, make, colour, shade laid on 20 mm thick cement Nortar 1.4 (1 cement + coarse sand) including grouting the joints with white cement mixed with matching pigment etc., complete. Image: Construct of Steel approved size, make, colour, shade laid on 20 mm thick cement Nortar 1.4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Image: Construct of Steel approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 13 (1 cement : 3 coarse sand) and jointing with grey cement slury @ 3.3kp or squi including pointing with grey cement slury @ 3.3kp or squi including pointing in with cement mixed with matching pigment complete. Image: Construct of Steel approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement mixed with matching pigment complete. Image: Construct of Steel app	17										
out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a cost of steel primers of approved make and manufacture Image: Cost of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a cost of steel primers of approved make and manufacture Image: Cost of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a cost of steel primers of approved make and laying vitrified floor this with double charge / multi charge printing with water absorption less than 0.5% and conforming to 15: 15622 of approved make in all colours and shades and size mentioned below (+/ 10 mm), laid on 20 mm thick cement mart 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Cost of the top		S. S. S. S.	factory made panel PVC door								
thickness and size of 19mm x 19mm for styles and 15x15mm for top & bottom rails M.S. frame shall have a coat of steel primers of approved make and manufacture Image: Constraint of the state of		~	shutter consisting of frame made								
thickness and size of 19mm x 19mm for styles and 15x15mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture Image: Constraint of the state of			out of M.S. tubes of 19 gauge								
19mm for styles and 15x15mm for top & bottom rails. M.S. frame shall have a coat of stele primers of approved make and manufacture Image: Constraint of the primers of approved make and manufacture Image: Constraint of the primers of approved make and manufacture Image: Constraint of the primers of approved make and manufacture Image: Constraint of the primers of approved make and manufacture Image: Constraint of the primers of approved make in all colours and shades and size mentioned below (+/ 10mm), laid on 20mm thick cement march 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigment set. complete. Image: Constraint of the primer of to the primer of the primatent of the primer of the primer of the prim											
Iop & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture Image: Steel primers of approved make and shades and size mentioned below (+/ 10mm) laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including growting the joints with white cement and matching pigments etc. complete. Image: Steel primers of approved make in all colours and shades and size mentioned below (+/ 10mm) laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including growting the joints with white cement and matching pigment etc., complete. Image: Steel primers of approved make in all colours and shades and size from the points with white cement and matching pigment etc., complete. Image: Steel primers of approved make in all colours and shades and size mentioned below (+/ 10mm) laid on 20mm thick cement and matching pigment etc., complete. Image: Steel primers of approved size, make, colours, shade laid on 20 mm thick Cement and matching pigment etc., complete. Image: Steel primers of approved size, make, colours, shade laid on 20 mm thick Cement and matching pigment etc., complete. Image: Steel primers of approved make, colours, shade sand size on woll and dadads over 12 mm thick bed of cement mixed with matching pigment etc., complete. Image: Steel primers of approved make, colours, shade sand size on woll and dadads over 12 mm thick bed of cement mixed with matching pigment etc., complete. Image: Steel pro											
shall have a coat of steel primers of approved make and manufacture Image: steel primers of approved make and primers of approved make and stee an			-								
approved make and manufacture Image: Second Sec											
152.2 Both side Pre-laminated panel PVC 2 2 2 2 0.80 2.10 3.36 - - 1 -											
door shutter 2 0.80 2.10 3.36 — 1 Providing and laying vitrified floor tiles with double charge / multi charge printing with water absorption less than 0.5% and conforming to 1S: 15622 of approved make in all colours and shades and size mentioned below (+/.10mm). laid on 20mm thick cement mortar 1:4 (1 cement :4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Conforming to 1S: 15622 of approved make in all colours and shades and size mentioned below (+/.10mm). laid on 20mm thick cement mortar 1:4 (1 cement :4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete. Image: Conforming to 1S: 15622 of approved make, colour, shade laid on 20 mm thick cement the conforming to 1S: 15622 of approved size, make, colour, shade laid on 20 mm thick cement mixed with matching pigment etc., complete. Image: Conforming to 1S: 15622 of approved make, colour, shade laid on 20 mm thick cement mixed with matching pigment etc., complete. Image: Conforming to 1S: 15622 of approved size, make, colour, shade laid on 20 mm thick cement mixed with matching pigment etc., complete. Image: Conforming to 1S: 15622 of approved make, colour, shade laid on 20 mm thick cement mixed with matching pigment etc., complete. Image: Conforming to 1S: 15622 of approved make, colours, shades and size on wall and datos over 12 nm thick bed of cement mixed with matching pigment conset sand) and jointing while cement mixed with matching pigment conset sand) and jointing while cement mixed with matching pigment conset sand) and jointing with grey cement slury @ 3.3kg per sqm including pointing in while cement mixed with matching pigment conset sand) and jointing with cement mixed with matching pigment conset sand) andj			approved make and manufacture								
Image: constraint of the point of the poi		152.2									
Image: 12.13Providing and laying vitrified floor tiles with double charge/ multi charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/-10mn), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: 100 million of the second secon			door shutter		0.00	2.10		0.06			
18 12.13 Providing and laying vitrified floor tiles with double charger multi charge printing with water absorption less than 0.5% and conforming to 1S: 15622 of approved make in all colours and shades and size mentioned below (+/ 10mm), laid on 20mm thick cement mortar 1:4 (1 cement at m matching pigments etc. complete. Image: Comparison of Co	_		=	2	0.80	2.10				2832.00	9515.52
tiles with double charge / multi charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1.4 (1 cement : 4 coarse sand) including prouting the joints with white cement and matching pigments etc. complete. Image: second	18	12.13	Providing and laying vitrified floor				Total	3.30	Juli	2032.00	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: Complete in the image is a second of the im	10	12.10						1			
absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/-10mm), laid on 20mm thick cement mortar 1:4 (1 cement i approved make colours) the joints with white cement attring pigment etc13.1Size 600x600mm16.0012.0072.0013.003.009.00											
conforming to IS: 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1.4 (I cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: Conforming to IS: 1 6.00Image: Conforming to IS: 1 6.00Image: Conforming to IS: 1 6.0013.1Size 600x600mmImage: Conforming to IS: 1 5622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1.4 (I cement mixed with matching pigment etc., complete.Image: Conforming to IS: 1 6.00Image: Conforming to IS: 1 6.00Image: Conforming to IS: 1 6.009.2Size above 300x300mmImage: Conforming to IS: 1 5622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1.4 (I cement mixed with matching pigment etc., complete.Image: Conforming to IS: 1 5622 of approved size, make, convert 12 mm thick bed of cement mixed with matching pigment etc., complete.Image: Conforming to IS: 1 5622 of approved size, make, convert 13 mm thick bed of cement Mortar 1.3 (I cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Conforming to IS: 1 5622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1.3 (I cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Conforming to IS: Conforming to IS: <td></td> <td></td>											
approved make in all colours and shades and size mentioned below (+/-10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.aaaaa13.1Size 600x600mm13.1Size 600x600mm14-16.0012.0072.00<											
shades and size mentioned below (+'. 10mm), laid on 20mm thick cement mortar 1:4 (1 cement a coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: Complete completeImage: Complete complete13.1Size 600x600mmImage: Complete completeImage: Complete completeImage: Complete completeImage: Complete complete13.1Size 600x600mmImage: Complete completeImage: Complete completeImage: Complete completeImage: Complete complete13.1Size 600x600mmImage: Complete completeImage: Complete completeImage: Complete completeImage: Complete complete1912.9Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete completeImage: Complete complete9.2Size above 300x300mmImage: Complete completeImage: Complete completeImage: Complete complete2012.7Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 co											
below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: Complete including including including including including including provided in the points with white cement and matching pigments etc. complete.Image: Complete including including including provided inc											
thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.Image: Second Secon											
13.1Size 600x600mm16.0012.0072.00113.1Size 600x600mm16.0012.0072.0011413.003.009.001115.2113.003.009.00111912.9Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.11											
the joints with white cement and matching pigments etc. complete.Image: second			-								
Image: section of the section of th											
13.1 Size 600x600mm Image: constraint of the second secon											
Image: constraint of the constra			matching pigments etc. complete.								
Image: state of the second sta		13.1	Size 600x600mm		1.0.0		10.00	70.00			
Image: second											
19 12.9 Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Image: Complete including complete including complete. Image: Complete including complete. 9.2 Size above 300x300mm Image: Complete including complete. Image: Complete including complete. Image: Complete including complete. 10 Image: Complete including complete including complete. Image: Complete including complete. Image: Complete including complete including complete. Image: Complete including complete. 10 Image: Complete including complete including complete including complete. Image: Complete including complete including complete including complete including complete including complete. Image: Complete including complete					5.00				Sqm	1151.00	93231.00
glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete interval including pointing interval including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete interval including pointing including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete interval including pointing including pointing to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement mixed with matching pigment complete.Image: Complete interval including pointing in white cement including pointing in white cemen	19	129	Providing and laying ceramic								
15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete image: Complete image	1)	12.9	alazed floor tiles conforming to IS:								
colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Colour, shade laid on 20 mm thick coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Colour, shade laid on 20 mm thick coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Colour, shade laid on 20 mm thick mixed with matching pigment etc., complete.9.2Size above 300x300mmImage: Colour, shade laid on 20 mm thick glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Colour											
Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete including pointing the joints with white cement mixed with matching pigment etc., complete.Image: Complete including pointing to IS including pointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Complete including pointing in white cement mixed with matching pigment complete.Image: Complete including pointing in white cement mixed with matching pigment complete.7.2Size above 200x300mmImage: Complete including pointing in white cement mixed with matching pigment complete.Image: Complete including pointing in white cement mixed with matching pigment complete.Image: Complete including pointing in white cement mixed with matching pigment complete.7.2Size above 200x300mmImage: Complete including pointing in white cement mixed with matching pigment complete.Image: Complete including pointing including pointing including pointing including pointing including pigment complete.Image: Complete including pointing including pointing including pointing including pointing including pigment complete.Image: Complete including pointing including pigment complete.7.2Size above 200x300mmImage: Complete including pigment com											
viewcoarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete.view <td></td>											
the joints with white cement mixed with matching pigment etc., complete.Image: complete integration of the second se											
mixed with matching pigment etc., complete.mixed with matching pigment etc., complete.mixed with matching pigment etc., complete.mixed with matching pigment etc., complete.9.2Size above 300x300mm23.002.4014.409.2Size above 300x300mm23.002.4014.4012.7Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Size above 200x300mmImage: Size above 200x300mm7.2Size above 200x300mm43.002.1025.20Image: Size above 200x300mm			,								
complete.											
9.2Size above 300x300mm23.002.4014.401114.40Sqm728.001042012.7Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.11 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>											
Image: 20 12.7Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Total14.40Sqm728.001047.2Size above 200x300mm43.002.1025.20 </td <td></td> <td>9.2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>		9.2									
2012.7Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Complete in the second seco				2	3.00				Sam	729.00	10483.20
glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.2.107.2Size above 200x300mm43.002.1025.20	20	127	Providing and fiving coramic				Iotal	14.40	Sqm	728.00	10483.20
15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.2.107.2Size above 200x300mm4	20	12.7									
shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment zomplete. 7.2 Size above 200x300mm 4											
over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Complete in the second se											
Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.Image: Complete in the second se											
sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.7.2Size above 200x300mm43.002.1025.20			- Section 19								
cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.2.107.2Size above 200x300mm43.002.1025.20											
including pointing in white cement mixed with matching pigment complete.2.107.2Size above 200x300mm43.002.1025.20											
mixed with matching pigment complete.abb7.2Size above 200x300mm43.002.1025.20											
complete. 2.10 25.20											
7.2 Size above 200x300mm 4 3.00 2.10 25.20											
		72			2.00		2.10	25.20			
	\vdash	1.4									
Total 45.36 Sqm 646.00 293									Sam	646.00	29302.56

Silver -									
21,	1.13	Providing and applying 2mm thick							
	State of the	ready mix exterior grade approved							
		make putty (like Birla wall care,						1	
		Alltek Superfine W/R of (NCL),							
		Asian, ICI, Nerolac, J.K. wall putty)							
		on walls to make the surface							
							 		
		smooth and even.		 					(00 10 01
				 		658.72	Sqm	94.50	62249.04
22	14.10	Wall painting with acrylic							
		premium emulsion (plastic) paint							
		of required							
		shade to give an even shade							
		On new work (two or more coats)							
		(, , , , , , , , , , , , , , , , , , ,							
						375.09	Sqm	44.50	16691.51
23	14.15	Painting exterior surface with							
		ACRYLIC SMOOTH exterior paint							
		of required shade as per							
		manufacturer's specifications to							
		give protective and decorative							
		finish including cleaning washing							
		of surface etc. complete with:							
	15.1	On new work (Two or more coats		 					
	15.1								
		applied @ 1.43 ltr/ 10 sqm over							
		and including priming coat of							
	1	exterior primer applied @ 2.20 kg/							
		10 sqm)				202 (2	Carro	56.00	15883.28
				 		283.63	Sqm	56.00	15005.20
24	14.22	Painting on new work (two or							
		more coats) to give an even shade							
		with:							
	22.1	Satin synthetic enamel paint							
		C.E	4	1.80	2.10	15.12			
		Do	12	1.50	1.50	27.00			
		D1	2	1.00	2.10	4.20			
					Total	46.32	Sqm	55.00	2547.6
25	14.23	Painting on old work (one or more							
		coats) to give an even shade with:							
	23.1	Satin synthetic enamel paint		 	1 50	10 50			
			6	 1.50	1.50			07.00	
				 	Total	13.50	Sqm	35.00	472.5
26	14.46	Removing old paint or polish by							
		paint remover or blow lamp or any							
		other means as approved							
		including preparing the surface							
		smooth after removing the paint.							
			6	 1.50	1.50				
1					Total	13.50	Sqm	32.50	438.7

and the second

1									
	24	Providing and fixing vitreous china							
21	CEL COL	inter closet (Furopean type w.c.							
		nan) with white ISI marked plaste							
		and lid 10 litre low level							
		white P.V.C. flushing cistern (same							
1		colour), conforming to IS : 7231							
		colour), comorning te				 			
		White pedestal type				 1.00	each	2882.00	2882.00
	4.1	white pedestal type				 1.00			
		Providing and fixing stainless steel							
28	18.20	AISI-304(18/8) wash basin with							
		C.l. brackets, 32 mm C.P. brass							
		waste of standard pattern,							
		including painting of brackets,							
		cutting and making good the walls							2276.00
		cutting and making good and				 1.00	each	3876.00	3876.00
		wherever required :				 1.00	Cuth		
	20.1	Size 450x380 mm							
29	18.25	Providing and fixing flexible P.V.C.			1				
		waste pipe for sink or wash basin							
		including P.V.C. waste fittings				1.00	each	68.50	68.50
		complete				 1.00	each		
	25.1	32 mm dia							
30	18.7	6 Providing and fixing on wall face					. 1		
		lor under floor UV stabilized							
		Unplasticised Rigid PVC pipes							
	1	(single socketed) having 3.2mm							
		wall thickness conforming to IS :							
		13592 (4kg/sqcm) including							
		required couplers, jointing with							
		seal ring conforming to IS : 5382 leaving 10 mm gap for thermal							
		leaving 10 mm gap for the the						0 (7 00	4005.00
		expansion etc complete				 15.00	metre	267.00	4005.00
H	76	2 110 mm dia pipe.							
F	1 10	Descriding and fixing on Wall lace							
	31 18.	Inv stabilized Unplasticised 110							
		accessories							
		hickness 101							
		Divid DVC nines conforming to 13.							1
		12592 (heavy) jointing with sear							
		laing conforming to IS: 5502							
		leaving 10 mm gap for thermal							
		expansion.							
		7.1 Tee/ Tee with door/ Bend 45°/	1						
Γ	77	7.1 Tee/ Tee with door/ Bend To 7						154.00	616.00
		Bend 90°	+			4.00	Each	154.00	
		.2 110 mm	1	1				44.00	44.00
	7	7.3 Vent covel	+			1.00	-		
		.2 110 mm				3.00			
	7	7.5 "P" trap 110mmx110mm long	-			3.00	Each	90.50	471.50
		7.6 Nahani trap 110x75 mm							
	32 1	9.5 Providing and fixing Chlorinated							
		Polyvinyl Chloride (CPVC) pipes,							
		having thermal stability for hot &							
		cold water supply including all	1						
		CPVC plain & brass threaded	1						
		fittings	_						

e of any discrepancy please inform the Completent Humbridge

1	ļ		ν ⁱ								
1								00.00		133.00	3990.00
Sillos	Sin Ca	Sim	5 mm nominal outer dia .Pipes.						metre	167.00	4175.00
-	1 5.	1	0 mm nominal outer dia .Pipes.						metre	284.00	2840.00
and a second	5.	4 3	2 mm nominal outer dia .Pipes					10.00	metre	204.00	201010
	-	12 0	Providing and fixing 15 mm								
33	3 19.		nominal bore Brass bib/stop cock								
			of approved quality:								1422.00
\vdash	13		Bib cock (350 grams)					6.00	Each	237.00	711.00
-			stop cock (350 grams)					3.00		237.00	7300.00
3	_		Providing and placing on terrace					1000.00	litre	7.30	/300.00
3	4 I I I		(at all floor levels) polyethylene								5
			water storage tank ISI : 12701								
			marked with cover and suitable								
			locking arrangement and making								
			necessary holes for inlet, outlet								
			and overflow pipes but without								
			fittings and the base support for								
L			tank								
13	35 2	20.6	Providing, lowering, laying,								
			aligning, fixing in position at and jointing at all level/ depths ISI								
			marked HDPE pipes of PE-100								
			grade and PN 6 for sewer								
			application as					10.00	metre	771.00	7710.00
ŀ	-+	6.2	150 mm dia					10.00	metre		
t	36	20.28	3 Providing and constructing brick								
			masonry chamber for								
			underground pipe and and bends								
			with well burnt modular clay bricks crushing strength not								
			ess than 35kg/cm2 in cement								
			mortar 1:4								
		28.1	0 Inside dimensions 455x610 mm								
		2012	and 45 cm deep for single pipe line								
			:	-				1.0) each	3796.00	3796.00
	\vdash		ELEC	CTR	ICAL	PAR	Г			ŀ	
				<u> </u>	1						
	37	3.1	Wiring for light/ fan/ exhaust fan /								
	3/	5.1	call bell point with 1.5								
			somm FR PVC insulated stranded								
			copper conductor single core cable								
			in concealed PVC conduit, with 5								
			amp piano type switch, phenolic								
			laminated sheet, suitable size M.S.								
			box and earthing the point with same size cable etc as required.								
			same size cable etc as required.								
		1.	1 Short Point						0 Point		1416.00
		1.							0 Point		1552.00
		1.	.3 Long Point					6.0	00 Point	553.00	3318.0

	alle a	Extra for providing and fixing light	1	1		2.00	Point	240.00	480.00
138	and and	blug point on board in				2.00		210.00	
/	1	concealed PVC conduit point							
		wiring with modular type 3							
		pin 5 amp socket outlet and 5 amp							
		switch including cost							
		of base and cover plate and G. I.							
		box etc. as required.							
39	3.13	Wiring for circuit/ sub main							C.
		wiring along with earth wire with							
		the following sizes of FR PVC							
		insulated copper conductor, single							
		core cable in concealed PVC						1	
		conduit as required.					Mtr	172.00	1376.00
\vdash	13.11	6 X 2.5 sq. mm in 25mm conduit				8.00		172.00	1032.00
		6 X 2.5 sq. mm in 25mm conduit				6.00	Mtr	172.00	
40	7.1	Supplying and fixing following							
40	7.1	piano type switch, socket,							
		other accessories on the existing							
		switch box/ cover including							
		connections etc. as required.				0.00	Feeb	178.00	534.00
-	1.12	Fan regulator Electronic, step type			1	3.00	Each	170.00	
	1.12	moving all round					_		
11	0.1	Supplying, installation, testing				1 1			
41	8.1	and commissioning of							
		and commissioning of							
		following sizes ceiling fan							
		including wiring the down rods							
		of standard length up to 30 cm							
		with 1.5 sq. mm FR PVC							
		insulated, copper conductor,							
		single core cable, earthing etc.							
		complete as required.			 	6.00	Each	1637.00	9822.00
	1.3	1400 mm sweep			 				
42		Supplying, installation, testing							
42	0.0	and commissioning of							
		following sizes heavy duty							
		(continuous running) 1400 rpm							
		exhaust fan in existing opening				1 1			
		in wall including earthing etc.				· 3			
		complete as required.							
						1.00	Each	2558.00	2558.00
	6.1	300 mm sweep							
43	8.22	Supplying, fixing, testing and							
		commissioning of following							
		LED lamps with inbuilt							
		electronic driver heat sink and							
		all other accessories in existing							
		holder/luminaries as							
		required and furnishing 2 Yrs							
		Guarantee certificate from							
		C				10.00	Each	973.00	9730.00
	0.10	9 Watt Supplying, fixing, testing and							
44	8.18	commissioning of following							
		CFL (Built in choke type) in							
		existing lighting luminaries as							
1	1	ICAISTING INSTITUTE FURTHER TOO NO	- 1						

a war	the second second									
F	Z	26 Watt					1.00	Each	289.00	289.00
-	18	85 Watt					1.00		907.00	907.00
45	8.19	Supplying, fixing, testing and	<u> </u>							
40	0.12	commissioning of following								
		CFL without ballast in existing CFL							2	
		lighting luminaries as								
		required.								
	19.5	36W CFL (without choke)	──				2.00	Each	176.00	352.00
							2.00	Lach	170.00	
46	8.29	Supplying, installation, testing and								
		commissioning of								
	1	following 230/250 volts CFL street								
		light fitting with perplex								
		cover on pole bracket complete but								
	1	without lamp as								
		required.			-		1.00	Each	1407.00	1407.00
	29.2						1.00	Laci		
47	8.34	Supplying, fixing, testing and								
		commissioning of following								
		230/250 volts metal halide lamp								
		in existing lighting luminaries								
		fixed on pole/ wall/ roof etc as								
		required.					1.00	Each	1403.00	1403.00
	34.	3 250 watt (T)					1.00	2		
4	8 9.1	0 Providing and fixing metal clad,								
		TP&N switch fuse unit (rewirable),								
		415/500 volts, with porcelain re-								
		wireble fuses								
		including drilling holes on the								
		board, connections, earthing the								
		body etc. as required. (Thimbeling								
		shall be paid separately).								
		2 (2	-				1.00	Each	1821.00	1821.00
F	10	 2 63 amps 1 Providing and fixing porcelain re- 	<u> </u>							-
1	49 9.1	wireble fuse carrier and								
		base unit on wooden board					1 1			
		including drilling holes on the								
		board, screws, connections etc. as								
		required. (Thimbeling				1				
		shall be paid separately).					1.00		157.00	157.00
F	11	.3 63 amps					1.00	Each	157.00	157.00
	50 11	.2 Supplying and fixing on surface/								
		recess following way, 240 volts								
		SP&N MCB distribution board of								
		sheet steel phosphatized and								
		powder painted complete with								
		tinned copper busbar, neutral								
		busbar, earth bar, din bar,								
		detachable gland plate, including								
		interconnections, earthing etc. as required. (But without								
		MCB/RCCB/Isolator)								
┝							1.00	Each	602.00	(02.00)
- 1	2	1 4 way. Single door	1	1	1	1	1.00	Eacil	002.00	602.00

	1 10							
1 -	12	Supplying and fixing DP MCB, 240						
	and the	olts, 'C' curve, suitable for lighting						
		and other loads in the existing						
		MCB DB complete with						
		connections, testing and						
		commissioning etc. as required.						
	12.3	40 amps		 	 2.00	Each	684.00	1368.00
52		Supplying and fixing SP MCB, 240		 				
		volts, 'C' curve, suitable for						
		inductive load in the existing MCB						
		DB complete with connections,						
		testing and commissioning etc. as						
		required.						
-	11.2	6 amps to 32 amps		 	 3.00	Each	154.00	462.00
53	14.2	Earthing with G.I. earth pipe 4.5		 	 1.00		3454.00	3454.00
33	14.2	metre long, 40 mm dia including						
		accessories, and providing						
		masonry enclosure with cover						
		plate having locking arrangement						
		and watering pipe etc. with						
		charcoal and salt as required.						
-	1110			 	8.00	Mtr	20.50	164.00
54	14.19	wire on surface or in						
		recess for loop earthing along with						
		existing surface/						
		concealed conduit/ submain	I					
		wiring/ cable as required.						
55	17.8	Supplying and laying following						
55	17.0	sizes one number PVC						
		insulated/ XLPE, PVC sheathed,						
		unarmoured, aluminium						
		conductor power cable of 1.1 KV						
		grade on surface/ existing cable						
		tray with 1 mm thick GI saddle as						
-	8.2	2 x 10 sq. mm			8.00	Mtr	88.00	704.00
-		4 x 10 sq. mm.			 9.00	Mtr	108.00	972.00
56		Supplying and fixing of 32mm dia				Each	823.00	823.00
50		x 2 metre long G.I pipe						
		(light) bracket for mounting street						
		light fittings of all types						
		on poles including bending the						
		pipe to the required shape, 2 Nos						
		40x3mm flat iron clamps with						
		bolts and nuts including wiring						
		with 1.5 sq. mm W.P /PVC wire etc.						
		as required.						
		as required.		 	 			
			_	 	 			

Sub Er.

Nagar Palik Nigam Korba

As per Estimate Amount Rs. Say Rs. 6.00.000 Astt. Fr. Nagar Palik Nigam Kortia

599741.78

~